

Xiv15 Reference Subwoofer (installation)



- **X Series Family-Lightweight**
- **Fixed installation**
- **Horizontal / Vertical / Cardioid**
- **No Rigging**
- **VDA18 / VDA12 Controller**

The Xiv15 is the recommended subwoofer for the X Series Line Array, M, TC, PS Series and other QANON AUDIO® products. It enhances the system's sub-low frequency supplement by enhancing the low-frequency throwing capability, which allows the system's operating frequency range to be extended to 30Hz.

The Xiv15 subwoofer is internally loaded with an 15-inch speaker. It has a powerful impact, sensitivity and low frequency performance, with a vented progressive shape on the inside and outside, allowing laminar airflow and reduced turbulence noise. These comprehensive features help to improve the working level. In the installation application, the Xiv15 is especially suitable for different needs. It can be installed in both mobile and fixed installations. It also provides both vertical and horizontal mounting methods, extending the extension of the low frequency limit, so that you can feel very full low frequency effect. For small rental activities, the Xiv18 and M, TC, and PS series are quick to deploy and easy to assemble. It can be used as a powerful PA speaker ultra-low frequency system, and its excellent projection capability can meet large space and multi-function hall.


Xiv15 Technical Specification

Type	Subwoofer
Frequency Response	30Hz-200Hz
Amplifier Recommend	VDA18 / VDA12
Preset	[Xiv15_100]
Horizontal	360°
Drivers	LF: 1×15" Ferrite 100mm voice coil
Handling Power (AES)	LF: 1000W
Maximum Peak SPL	135dB/1m
Nominal Impedance	LF:8Ω
Connections	2 x NL4 SpeakOn
Pin Connections	NL4=LF:+1-1
Height Front	500mm
Height Back	500mm
Width	430mm
Depth	600mm
Weight	31kg / 68.3lb
Handle	2 ergonomic handles
Antiskid	4 ground runners
Fastener	N/C
Material	Baltic Birch Plywood
Finish	Dark Grey
Front	Polyester powder-coated steel grill
Rigging	Steel
Protection rating	IP45


430mm [16.94"]



Front



Side



Top