

## Xiv18 Reference Subwoofer (installation)



- X Series Family-Lightweight
- **■** Fixed installation
- Horizontal / Vertical / Cardiol
- No Rigging
- VDA18 / VDA12 Controller

The Xiv18 is the recommended subwoofer for the X Series Line Array, M, TC, PS Series and other QANON AUDIO® products. It enhances the system's sub-low frequency supplement by enhancing the low-frequency throwing capability, which allows the system's operating frequency range to be extended to 25Hz.

The Xiv18 subwoofer is internally loaded with an 18-inch speaker. It has a powerful impact, sensitivity and low frequency performance, with a vented progressive shape on the inside and outside, allowing laminar airflow and reduced turbulence noise. These comprehensive features help to improve the working level. In the installation application, the Xiv18 is especially suitable for different needs. It can be installed in both mobile and fixed installations. It also provides both vertical and horizontal mounting methods, extending the extension of the low frequency limit, so that you can feel very full low frequency effect. For small rental activities, the Xiv18 and M, TC, and PS series are quick to deploy and easy to assemble. It can be used as a powerful PA speaker ultra-low frequency system, and its excellent projection capability can meet large space and multi-function hall.

## **Xiv18 Technical Specification**

Туре	Subwoofer
Frequency Response	25Hz-200Hz
Amplifier Recommend	VDA18 / VDA12
Preset	[Xiv18_100]
Horizontal	360°
Drivers	LF: 1×18" Ferrite 100mm voice coil
Handling Power (AES)	LF: 1200W
Maximum Peak SPL	136dB/1m
Nominal Impedance	LF:8Ω
Connections	2 x NL4 SpeakOn
Pin Connections	NL4=LF:+1-1
Height Front	650mm
Height Back	650mm
Width	550mm
Depth	700mm
Weight	44kg / 97lb
Handle	2 ergonomic handles
Antiskid	4 ground runners
Fastener	N/C
Material	Baltic Birch Plywood
Finish	Dark Grey
Front	Polyester powder-coated steel grill
Rigging	Steel
Protection rating	IP45





