



V-PSP Signal network





V-PSP Signal network

V-Panel

1U distribution of front panel includes four power amplification controllers for analog audio signal and digital audio signal. Four channel analog signal link out and three channel stereo AES / EBU link out link other rack signals. The front panel analog connector 4-channel XLR input and output is compatible with the rear 4-channel output, and the panel also has a 2-ethercon I / O connector connected to the network to allow reception.

Cables

- 4 x ANALOG OUT XLR3 male/female cables (0.8m)
- 3 x AES OUT XLR3 male/female cables (0.8m)
- 3 x AES LINK XLR3 male/female cables (0.8m)
- 2 x CAT5e U/FTP cables(0.8m)
- 2 x CAT5e U/FTP bridge cables(0.25 m)



Technical Specification

Front connectors

Analog Input/Link	4 x female Neutrik® XLR3 (IN) 4 x male Neutrik® XLR3 (LINK)
AES/EBU Input/Link	3 x female Neutrik® XLR3 (IN) 3 x male Neutrik® XLR3 (LINK)
Network	2 x etherCON® (IN/OUT)

Rear connectors

Analog Output	4 x female Neutrik® XLR3 (Out)
AES/EBU Input/Link	3 x female Neutrik® XLR3 (IN) 3 x male Neutrik® XLR3 (LINK)
Network	2 x etherCON® (IN/OUT)

Physical data

Dimensions (W x H x D)	483 x 44 x 123 mm
Material	Metal
Finish	Black
Protection rating	IP2x
Weight	2kg / 4.4lb



V-Panel Dimensions CAD

