

Voe-L Ultra Compact Extend woofer



Voe-L is a recommended subwoofer for Voe line arrays and other QANON AUDIO < products. It adds to the sub-low frequency of the system by enhancing the throwing ability of the low frequency. It allows the operating frequency range of the system to be extended to 30Hz.

The Voe-L Extended Low Frequency Loudspeaker contains an 18-inch speaker. It has strong impact force, sensitivity and low frequency efficiency. Its internal sides have H-shaped vent progressive shape, allowing laminar flow and reducing turbulent noise. These comprehensive characteristics help to improve the working level.

The Voe-L subwoofer can be used as an independent array or fly at the top of a vertical array composed of Voe line arrays. Voe-L is driven and amplified by C15 or VDA18/VDA14/VDA12 power controller. Protect and optimize different configurations of loudspeaker systems, including cardioid.

- **V Series Family - Lightweight**
- **Touring - Installation**
- **Voe Extend Woofer**
- **VDA Controller / VS28 Subwoofer**



Voe-L Technical Specification

Type	Ultra compact Extend woofer
Amplifier Recommend	VDA18 / VDA14 / VDA12 / C15
Frequency Response (Preset)	30Hz [Voe_100/C] [Voe_125/C] Preset
Horizontal	360°
Angle Increments (Voe)	-1° - 2° - 3° - 4° - 5°
Angle Increments (Voe)	0° +1° +2° +3° +4° +5° +6° +8° +10°
Drivers	LF:1×18" Neodymium
Handling Power (AES)	LF : 1400W
Maximum Peak SPL	138dB/1m
Nominal Impedance	LF:8Ω
Connections	2 x NL4 SpeakOn
Pin Connections	NL4=LF:+1-1
Height Front	550mm
Height Back	550mm
Width	700mm
Depth	700mm
Weight	63kg / 139lbs
Handle	4 ergonomic handles
Pole socket	1 x 35mm Pole socket
Fastener	6 side fastener
Material	Baltic Birch Plywood
Finish	Dark Grey
Front	Polyester powder-coated steel grill
Rigging	Steel
Protection rating	IP45

